




IDOT HMA Update

David L. Lippert, P.E.

Engineer of Materials and Physical Research
Illinois Department of Transportation


Illinois Asphalt Paving Association



PG Liquid Binder Usage


PG Binder Used in 2010 (thousand tons)

Tons of Binder




% Polymer Usage - 2003 to 2010

Percent Polymer



% Grades Used - last 5 years




AC Price Index


- Based upon largest suppliers of previous year
- Prices submitted as of first of each month
- Average = Index
- BMPR Policy Memo 1-08.0
 - PERFORMANCE GRADED ASPHALT BINDER ACCEPTANCE PROCEDURE

IDOT AC Price Index Bases

AC/Crude/Gasoline Price Comparison




AC/Crude/Gasoline Price Comparison




Liquid AC Sampling at HMA Plants



Sampling Points – Let's Count the Ways



Sample at closest point to the mix - at Injection Line



District PG Investigative Field Samples

As of 12/31/10

District	Sample Total	Off Test	% Off Test
1	654	12	1.8
2	215	4	1.9
3	121	1	0.8
4	223	0	0
5	176	0	0
6	227	2	0.9
7	209	1	0.5
8	249	7	2.9
9	122	2	1.6

FINE MIX ASPHALT

Fine Mix HMA

- ⦿ Less large stone on large stone
- ⦿ Relies on crushed fine on fine fractions
- ⦿ Larger stone floats in matrix to help reduce AC content
- ⦿ Why?
 - Better compaction – especially at joints
 - Less permeable
 - Longer life

Future Roll Out Fine Graded

- ⦿ Slow – more trials 2011
- ⦿ Collect data on lay down
 - Permeability
 - Density
 - Hamburg
- ⦿ Review
- ⦿ Possible trial project in each District for 2012

Safety Edge





30°

Safety Edge at IDOT

- ▶ Including in new contracts
 - Starting with State Contracts
 - LRS to follow
 - For pavements with no shoulder up to 3' shoulder
- ▶ Want to see proven devices used
 - Strike off plates not allowed per spec
 - Must compact and produce consistent durable edge
 - If can't produce desired edge – deduct tonnage from pay if material is wasted.

Warm Mix Asphalt

Hot

Warm



Pre Exp. Feature Work Plan 7

2008-2009 WMA Projects 7


2010 WMA Projects 7

Total number of warm mix contracts 21

Over 50,000 tons WMA

Hamburg Wheel Testing

Warm Mix Asphalt Projects 2010



Background

Drivers

- Federal Highway Administration
Every Day Counts Innovation
Initiative, Industry, and
Environmental Sustainability



Goal:

- Generation of Permissive Use Specification
- Specification to allow use of additives as well as foaming technology
- Additives (mineral, chemical, or organic) to be selected from “Pre Approved” list maintained by BMPR

Permissive Use Specification

- Embrace WMA
- Allow bidding up front
- Allow approved additives plus foam
- Start with N_{70} and below

Time Frame

- Drafting permissive use specification
- May/June - Comments and discussion incorporated from Districts, FHWA, and Industry - BMPR Spec
- July - Submit to Design and Environment
- Effective Jan. 1, 2012
- Bulk of 2011 - Contractor's Proposal

A close-up photograph of a large pile of dark, broken asphalt shingles. The shingles are fragmented into various sizes and shapes, showing the layered structure of the material. The background is a dense, dark mass of these fragments.

Reclaimed Asphalt Shingles (RAS)

HB 1326 HA 03

SB 1543 SA 01

- Shingles - No land filling within 30 miles of recycler
- CDD: Credit of 2 for 1 tons shingles recycled for 75% recycle goal
- ILEPA to manage asbestos program
- Requires allowing shingles in state highway construction
- Shall meet or exceed maximum percentage of shingles allowed by Tollway
- Maximize the use of recycled aggregates and other constituents in the mix

More HA 3/SA 01

- Reduce carbon footprint
- Extend the paving season
- Regional Engineers to report at hearings annually
 - Usage
 - Cost savings
 - Performance
- HMA Producer
 - Shall not use shingles unless asbestos tested
 - Must meet ILEPA Section 22.54 if doing own processing

RAS Status

- Specification developed last year for state wide use
 - Revised – Effective March 1, 2011
- Policy developed last year
 - BMPR Policy Memo issued August 13, 2010
 - Requires testing of all tear off material for asbestos
 - Current versions differs from Tollway's 1 test/250 ton
- Harmonization effort with Tollway
 - Legislation has effort on hold pending outcome
 - Asbestos testing final issue
- Consultant on board to assist IDOT on asbestos

SB 1735
HB 1283



SB 1735/HB 1283

- Department QC/QA training program materials to be available to apprenticeship programs
 - Course curricula
 - Teaching slides
 - And other materials to teach classes
- Third party testers provided with 10 days notice
- Department to certify as able to teach/train own members

RAP/RAS Maximum Shift

Percent AC Replacement

- Specification becoming complex
 - RAP Percent
 - RAS Percent
 - When to grade bump?
- Greatly increasing amount of recycled material
- Changed percent RAP replacement to liquid “binder” replacement
- BMPR RAP spec revised 3/1/11

Old Usage of FRAP

HMA Mix	Level 1 Max % FRAP		
N Design	Binder/LB	Surface	Poly Mod
30	35	35	10
50	30	25	10
70	25	20	10
90	20	15	10
105	10	10	10

New Binder Replacement

HMA Mix	Level 1 Max % Binder Replacement FRAP+RAS		
N Design	Binder/LB	Surface	Poly Mod
30	35	35	10
50	30	25	10
70	25	20	10
90	20	15	10
105	10	10	10

Increasing usage of FRAP+RAS

HMA Mix	Level 2 Max % Binder Replacement FRAP+RAS		
	Binder/LB	Surface	Poly Mod
N Design			
30	40	40	10
50	40	30	10
70	30	20	10
90	30	20	10
105	30	15	10

Use Hamburg Wheel if over Level 1


Hamburg Wheel



Hamburg Wheel

50 Passes/Minute

158 Lbs



50 C


AASHTO T-324

Hamburg!



10 13:24

Specimen Prep






Fail



Pass

SLOW Implementation Schedule

The background of the slide features a faded, historical-style photograph. It depicts a grand, multi-story building with a prominent clock tower and ornate architectural details. In the foreground, a street scene is visible with several horse-drawn carriages and people, suggesting a historical or theme park setting.

- 2011
 - High Replacement RAP and RAS
 - Permissive use Warm Mix
- 2012 - 2013
 - Other New mixes (fine graded) and Renewals
- 2014 on
 - Full Implementation





Grade Bumping

Grade Bumping is Critical


- Low amounts of AC replacement can be tolerated with little or no impact
- Around 20% replacement mix properties are impacted
 - Grade bumping policy
 - Above 20% - Double bump down
 - PG64-22 to PG 58-28
 - If not followed – shorter pavement life due to cracking

% Grades Used - last 5 years





PG Grade vs. Replacement AC



Life Cycle Cost Audit

Audit

- 20 ILCS 2705/2705-590
 - Requires Life Cycle Costing (LCC) on all projects over \$500,000
 - Award construction to lowest LCC
 - Models based upon data
 - If don't have data may use other similar states data
- Audit to determine if IDOT following law



The End



Questions??