

Illinois Tollway – Materials Update

Steven L. Gillen, Manager of Materials, Pavements and
Construction Research

Illinois Asphalt Pavement Association, March 11, 2013

Recycling Will Continue to Grow

Fractionated RAP
(FRAP)



Recycled Asphalt Shingles (RAS)



“Selling” FRAP



Dr. Don Brock



2007 FRAP Research Goals and Results

- ✓ Quality control maintained
- ✓ Retain long-term performance at lower costs
 - ▶ Fatigue and Dynamic Modulus analysis
 - ✗ Are mix properties compromised with higher RAP?
 - ▶ How soft for the PG? (64-22? vs. 58-22 vs. 58-28)



2011 – 2013 FRAP Research with Concrete

- ▶ Durability of concrete using Tollway FRAP will be adequate for composite pavement applications
- ▶ Durability of concrete using IDOT FRAP is currently being studied



Tollway RAS Research

- ▶ Collaborative effort
 - ▶ Illinois Environmental Protection Agency
 - ▶ U.S. Environmental Protection Agency
 - ▶ RAS FHWA Pooled Fund
- ▶ Field production tests
- ▶ Research results



IDOT RAS Research



Tollway Asphalt Binder Replacement

- ▶ SMA – 40 percent
- ▶ Shoulder Surface – 40 percent
- ▶ Shoulder Binder – 50 percent
- ▶ Asphalt Subbase – 65 percent




Tollway WMA - 2012

- ▶ 762,000+ total tons
- ▶ SMA mainline
 - ▶ 304,000 tons
- ▶ N50 Shoulder Binder
 - ▶ 204,000 tons
- ▶ N70 Shoulder Surface
 - ▶ 210,000 tons
- ▶ Stabilized Subbase
 - ▶ 8,400 tons



Tollway WMA - 2012

- ▶ 10 different plants
- ▶ 2 used chemicals
 - ▶ Evotherm (4)
 - ▶ Rediset LQ (3)
- ▶ 3 used water injection
 - ▶ ASTEC (1)
 - ▶ MAXAM AQUABlack (1)
 - ▶ Stansteel Accu-Shear (1)



Tollway WMA - 2012

- ▶ High recycle in Tollway WMA:
- ▶ SMA
 - ▶ All used RAS (2 GTR, 7 SBS)
 - ▶ ABR – 31 to 38%
- ▶ Shoulder Binder and Surface
 - ▶ ≈ Half used RAS
 - ▶ Binder ABR – 33 to 50%
 - ▶ Surface ABR – 30 to 40%
- ▶ Stabilized Subbase
 - ▶ Both used RAS; both had 64% ABR
 - ▶ RAS needs higher temperature



WMA Lessons Learned

- ▶ Mix temperature ranges
 - ▶ Mix type
 - ▶ Shoulder mixes and moderate RAP: 250 - 270F
 - ▶ Shoulder mixes with RAS: 280 – 300 F
 - ▶ SMA with RAS: 280 – 320F
 - ▶ Plant and personnel
 - ▶ Weather (night, day, summer, fall)

WMA Lessons Learned

- ▶ Contractor Learning Curve – some: steep
- ▶ All technologies “performed” effectively
- ▶ Industry-wide: plant operations need reviewing to fully implement WMA
 - ▶ Flighting, air flow – for both WMA and high recycle
 - ▶ Combination of high recycle and lower temperatures
 - ▶ Stress on motors from stiff mixes (SMA + RAS + modified PG)

WMA – Moving Forward

- ▶ Contractor
 - ▶ Personnel need to become comfortable with the practice
 - ▶ Plant “optimization” to incorporate WMA and high recycle
 - ▶ Investigation of benefits
 - ▶ Lower energy
 - ▶ Compaction aid



WMA – Moving Forward


- ▶ Suppliers
 - ▶ WMA processes have to be made more compatible with RAS containing mixes to make the materials more workable at lower temperatures



WMA – Moving Forward

- ▶ Agencies
 - ▶ Proven to improve performance
 - ▶ Better definition of “Warm Mix” needed
 - ▶ Temperature only?
 - ▶ Simply “use of the technology” ?
 - ▶ Mix variables (RAP, RAS, modified PG)
 - ▶ Combination of Warm Mix and RAS
 - ▶ Minimum temperature needed for RAS?
 - ▶ RAS + Rejuvenators?

Tollway Reconstruction: I-90



- ▶ 2013-2014
 - ▶ I-39 to Elgin
- ▶ 2014-2016
 - ▶ Elgin to O'Hare
- ▶ Asphalt Subbase
- ▶ Asphalt Shoulders

2013 Veterans Memorial (I-355) Rehabilitation

- ▶ Between I-55 and 83rd Street
- ▶ Collector and distributor roads at Butterfield Road
- ▶ Mainline roadway in both directions between Army Trail Road and Fullerton Avenue



Elgin O'Hare Western Access



Tri-State Tollway (I-294)/I-57 Interchange



NAPA Environmental Leadership Award





THANK YOU
