



IDOT HMA Update 2014

Matthew Mueller, P.E.

Bureau of Materials and Physical Research

Illinois Department of Transportation

Illinois Asphalt Paving Association

Design

Materials

Construction

Acceptance

Training

Research

Challenges

Reduction in Number of Mixes Designs

Reduction in Number of Designs

- Eliminate
 - N₁₀₅ Binder and Surface - IN PROGRESS
 - IL-12.5 Surface Mixes – IN PROGRESS
 - N₃₀ “All Other Mixes” (i.e. 2% Voided BAM for stabilized sub-base and shoulders)
 - IL-19.0 Coarse Graded Mixes
- ABR & Percent of RAP / FRAP / RAS
 - Developed Committee to Address

HMA Fine Graded 19.0 Mix

Fine Graded 19.0 Mix

- Agreed at Joint HMA TWG to Abandon Coarse Graded IL-19.0 & go with Fine Graded IL-19.0
- BMPR Revised BDE Special *Mixture Design Composition and Volumetric Requirements*
 - Redefines our current IL-19.0 to be less coarse
 - Eliminates reference to N105 & 12.5 **Surface** Mix
 - Target November 2014 Letting as BDE
 - BMPR Special until then


New ABR spec

- The focus is on Asphalt Binder Replacement and not on how much RAP/FRAP or RAS is incorporated.


PG Liquid Binder Usage



% Polymer Usage



PG Binder Used (in thousand tons)



Liquid AC Sampling at HMA Plants



2013 District PG INV Field Samples

District	Sample Total	Off Test	% Off Test
1	419	17	4.1
2	72	3	4.2
3	52	0	0
4	81	1	1.2
5	98	0	0
6	100	2	2.0
7	145	1	0.7
8	164	0	0
9	110	1	0.9
TOTAL	1241	25	2.0 %

Potential PG Binder Changes

- Softer grades of PG binder
 - PG40-40, PG52-34
- Reintroduction of Recycled Engine Oil Bottoms (ReOB) to binder
 - Cost/Benefit, method of measurement
- Classification of binder using MSCR in lieu of PG testing
 - Grade to high temperature of location
 - Mix performance unknown
- Asphalt Binder Replacement (ABR) rejuvenators

Agg Issues

- Fine graded mixes creating too many fines.



Contractor Labs

- Round robin testing of Gmm, Gmb, Voids, unconditioned and conditioned tensile strengths with Z-score.
- AMRL may begin round robin testing of Hamburg Wheel in 2016.

Longitudinal Joint Issues




Failing PFP Edge Densities

- Rapid Penetrating Emulsion
 - Used on D1, D2 & D6 PFP projects
 - Guide will be developed for RPE
 - Proposed use of RPE would be as follows:


Effect of In-Place Voids on Life

Washington State DOT Study




Effect of In-Place Voids on Life

Washington State DOT Study




Effect of In-Place Voids on Life

Washington State DOT Study




Effect of In-Place Voids on Life

Washington State DOT Study




Effect of In-Place Voids on Life

Washington State DOT Study




Effect of In-Place Voids on Life

Washington State DOT Study




Effect of In-Place Voids on Life

Washington State DOT Study




Effect of In-Place Voids on Life

Washington State DOT Study



Effect of In-Place Voids on Life

Washington State DOT Study





Surface Mix – Erase Penalties If:




Figure 5. Field Permeability-Density Relationship for 9.5 mm NMAS Mixtures

Binder Mix – Erase Penalties If:




Figure 3. Field Permeability-Density Relationship for Project 11 (19.0 mm NMA S Mix)

Paver Segregation

- Anti-segregation kits



4








The Future of Longitudinal Joints ??

- Require Longitudinal Joint Seal for all C/L Joints Unless:
 1. Lift Paved Against a Confined Edge
or
 1. Full Width or Echelon Paving (i.e. no C/L Joint)
or
 2. Remove Low Density Mat'l from Unconfined Edge (i.e. Trim Off 6 inches)

Longitudinal Joint Seal 12 Yrs Later



Longitudinal Joint Seal 12 Yrs Later



Material Transfer Device Proposed Specification

Current Spec

- MTD w/ > 20 psi contact pressure not allowed on lower lifts of a full depth HMA pavement until 10 in. thickness in place.

Proposed Spec

- Require an MTD on all lifts of a Full Depth pavement.
- Only MTD's with contact pressure ≤ 25 psi allowed on lower lifts where < 10 inches in place.
- Spec will be drafted & sent to BDE.

Tack Coat Spec Status




2013 Experience

- Not Enough Tack Coat being Applied
 - Jobs visited Tack Coat was $< \frac{1}{2}$ the specified rate.
- Improper Cleaning
 - Vacuum Sweeper either not being used or
 - Wrong type of Vacuum Sweeper.

Still Not Enough



Bond Strength vs Residual Asphalt Application Rate



Current Tack Coat Spec

- BMPR Special is on the Website
- Latest Revisions:
 - “Vacuum sweeping shall be accomplished with a regenerative air vacuum sweeper.”
 - “A bituminous prime coat shall be applied between each lift of HMA according to Article 406.05(b).”
 - “The regenerative air vacuum sweeper shall blast re-circulated, filtered air through a vacuum head having a minimum width of 6.0 feet at a minimum rate of 20,000 cubic feet per minute.”

Regenerative Air Vacuum Sweeper



What's Next?

- Monitor success of pavement cleaning with brooming and air blasting or sweeping.
- Test additional emulsions for applicability to rapid set.
- Monitor the use of “spray pavers”.
- Target 2015 as BDE Special.
- Correct terminology from Prime Coat to Tack Coat for next Spec Book.



Hamburg Wheel

Hamburg Spec

- Effective Nov. 2013 Letting – All mixes must pass Hamburg Wheel

*HMA – Mixture Design Verification and
Production*

Hamburg Spec

- Production – A 300 ton Test Strip will be required at the beginning of HMA production
 - for each Mixture with 3000 tons or more
 - for each Contract
 - The 300 tons are excluded from pay adjustments on QCP and PFP. However, requirements of Section 406 still apply.

Hamburg Spec

- Required Hamburg Wheel Test (run by Dept). If Hamburg Test fails, production shall cease.
 - All prior produced material may be paved out, if other mix criteria met.
 - No additional mix produced until Engineer receives passing Hamburg Wheel test from Contractor.

2013 PFP Summary

2013 PFP Projects

District	Projects	Tons	% Jobsite
1	24	351,596	0
2	0	0	N/A
3	2	34,727	100
4	2	19,509	100
5	3	48,800	100
6	2	54,378	100
7	7	155,000	100
8	4	89,000	100
9	3	52,381	100
Total	47	981,396	

Nov 1, 2013

2013 PFP Average Pay

- Binder = 98.6
- Surface = 99.5
- Overall = 99.1

PFP Issues

- Low Longitudinal Joint Density
 - Numerous ½ mile sections had pay deducts according to PFP Pay Adjustment Table or required **Remedial Action**
 - Most sections needing Remedial Action were treated with Rapid Penetrating Emulsion (RPE)

PFP Spec Revisions for 2014

- Editorial Cleanup
- Remove wording that PFP cannot be used on Shoulders
- PFP Spec Stable Δ will become a BDE Special for November Letting

2013 QCP Summary

2013 QCP Projects

- 31 Mixtures Completed
- 211,680 Tons
- Average Pay = 99.7%
- Range => 96.4% – 100%
- Department Tested 53.0% of Samples

QCP Spec Revisions for 2014

- Allow the subplot size to be adjusted by project.
- Revised Pay Document to allow yd^2 pay item.
- Eliminate Dust/AC Precision Limit.
- Added footnote to Dust/AC Pay Table that District will test all 4 sublots if Dust/AC out-of-spec.



Local Agency Acceptance



Local Agency Acceptance

One Scenario

PFP

QCP

Quality Managed Plant (QMP)

- Specification
 - QA by Local Agency
 - Mix from a Qualified Plant
 - District splits samples once/month or 10,000 tons per plant
 - District monitors problems
 - District coordinates round robin testing

HMA Inspection Course (a.k.a. - RE Training)

HMA Inspection Course

- One day course developed for & being taught in all Districts this spring
- Targets PI (Materials & Construction) personnel
- Emphasis on:
 - PFP & QCP Duties
 - Jobsite Sampling
 - Longitudinal Joints
 - New Tack Coat Spec
 - Paver Segregation
- Future of Course – department STTP class

HMA Toughness/Brittleness Test

- ICT project, Prof. Imad Al-Qadi
- Testing Protocols to Ensure Performance of High Asphalt Binder Replacement Mixes Using RAP & RAS Project ID: R27-128
- Fatigue?
- Cold weather Thermal Cracking?





Future Challenges





Rubblizing and Full Depth HMA

